




## Medium Flood 400 200 ft ft Ø ø 3.0 1.41 3.0 2.03 9.0 9.0 6.09 4.22 7.04 15.0 15.0 <u>10.15</u>



## Flaxo Pendant Light

Flaxo is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

Model/Colors	Available in White & Black.
Application Areas	Pendant Light For Indoor Applications. Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

## **TECHNICAL PARAMETERS**

Voltage	100 - 277 V AC, 50-60 Hz	
IP Rating	IP65	
Light Source	Osram SOLERIQ S 19	
Operating Position	No Swiveling Type	
Start Time	Instant	
Driver	Stand Alone (included)	
Optics	Reflective Cup Structure	
Beam Spread	Medium, Flood	
Dimming	Triac Dimming / 0-10 V Dimming	

CRI	Power (W)	CCT (K)	Total Lumen Output (Im)	Beam Spread
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	2700	640 / 1200 / 1800 / 2400 / 3200 / 4000 / 4400	20º / 40º
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	3000	680 / 1275 / 1700 / 2550 / 3400 / 4250 / 4675	20º / 40º
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	4000	720 / 1350 / 1800 / 2700 / 3600 / 4500 / 4950	20º / 40º
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	5000	760 / 1425 / 1900 / 2850 / 3800 / 4750 / 5225	20º / 40º

## Note

1. Product available in other Kelvin temperatures on request.

info@ikioledlighting.com | +1 844-533-4546 | www.retail.ikioledlighting.com

