

Mica

Pendant Light



Mica is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.


Model/Colors | Available in White.

Application Areas | Pendant Light For Indoor Applications.
Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance


TECHNICAL PARAMETERS

Voltage	100 - 277 V AC, 50-60 Hz
Light Source	Osram SOLERIQ S 19
Operating Position	No Swiveling Type
Start Time	Instant
Driver	Stand Alone (included)
Optics	Reflective Cup Structure
Beam Spread	Spot, Medium, Flood
Dimming	Triac Dimming / 0-10 V Dimming

Spot		Medium		Flood	
15°		30°		45°	
ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15.0	10.15




8 W



15 W - 20 W



30 W



40 W

CRI	Power (W)	CCT (K)	Total Lumen Output (lm)	Beam Spread
>90	8 W / 15 W / 20 W / 30 W / 40 W	2700	640 / 1200 / 1600 / 2400 / 3200	15° / 30° / 45°
>90	8 W / 15 W / 20 W / 30 W / 40 W	3000	680 / 1275 / 1700 / 2550 / 3400	15° / 30° / 45°
>90	8 W / 15 W / 20 W / 30 W / 40 W	4000	720 / 1350 / 1800 / 2700 / 3600	15° / 30° / 45°
>90	8 W / 15 W / 20 W / 30 W / 40 W	5000	760 / 1425 / 1900 / 2850 / 3800	15° / 30° / 45°

Note

- Product available in other Kelvin temperatures on request.
- Ceiling cup standard size: 4-3/4"; Cable standard length: 2ft