

# Glint

## Downlight



Glint, a circular shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.


**Model/Colors** | Available in White.

**Application Areas** | Guest Room, Corridor, Restaurant, Meeting Room  
Club, Hall, Hotel Entrance


### TECHNICAL PARAMETERS

<b>Voltage</b>	100 - 277 V AC, 50-60 Hz
<b>Light Source</b>	Osram SOLERIQ S 19
<b>Operating Position</b>	Swiveling Type
<b>Start Time</b>	Instant
<b>Driver</b>	Stand Alone (included)
<b>Optics</b>	Darklight Technology Black, Silver
<b>Dimming</b>	On-Off / Triac / 0-10 V


Spot		Medium		Flood	
15°		24°		38°	
ft	ø	ft	ø	ft	ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15.0	10.15




8 W - 15 W




20 W



40 W



50 W



55 W

CRI	Power (W)	CCT (K)	Total Lumen Output (lm)	Beam Spread (Options)	Finish
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	3000 K	1010 / 1895 / 2527 / 3790 / 5054 / 6318 / 6950	15° / 24° / 38°	White
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	4000 K	1060 / 2000 / 2660 / 3990 / 5320 / 6650 / 7310	15° / 24° / 38°	White
>90	8 W / 15 W / 20 W / 30 W / 40 W / 50 W / 55 W	5000 K	1120 / 2100 / 2800 / 4200 / 5600 / 7000 / 7700	15° / 24° / 38°	White

#### Note

1. Product available in other Kelvin temperatures on request.
2. Reflector Colour- Black, White, Silver, Golden available.