


## Alem Track Light



Model/Colors Available in White & Black.


**Application Areas** Track light for indoor applications.

## TECHNICAL PARAMETERS

Voltage	100 - 277 V AC, 50-60 Hz		
Light Source	Osram SOLERIQ S 19		
Operating Position	Swiveling Type		
Start Time	Instant		
Driver	Stand alone (included)		
Beam Spread	Spot, Medium, Flood, Wide Flood		
Dimming	Triac Dimming		



Spot		Mediu	Medium		Flood		Wide Flood	
	15º		240		380		60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	



CRI	Power (W)	CCT (K)	Total Lumen Output (Im)	Beam Spread (Options)	Finish
>90	20 W / 30 W	2700 K	2800 / 4200	15º / 24º / 38º / 60º	White / Black
>90	20 W / 30 W	3000 K	2900 / 4250	15º / 24º / 38º / 60º	White / Black
>90	20 W / 30 W	4000 K	3000 / 4350	15º / 24º / 38º / 60º	White / Black
>90	20 W / 30 W	5000 K	3100 / 4550	15º/24º/38º/60º	White / Black

## Note

1. Product available in other Kelvin temperatures on request.

